

6000 SERIES WALL MOUNT FIBER TERMINATION UNIT

DESCRIPTION

Wall Mount Fiber Management unit from AFS provides environmental and mechanical protection for fiber and inter connect components. Easy to use, this system assists in the function of splicing and patching with neat fiber organisation and reduces the risk of fiber disturbance during installation or re-entry.

Different options are available to give a wide variety of configurations to meet individual network specifications

REDUCED INSTALLATION COST

AFS can supply units with Pigtails, Patchcords and Adapters configured to your requirements which are ready to splice using fusion splicing.

APPLICATION

6000 Series Fiber distribution unit is typically located at the customers' premises for termination of fibers.



FEATURES

1. Wall mountable
2. Detachable door
3. Lockable door
4. Colour coded buffer tubes
5. Special cable glands
6. Four cable entry ports

BENEFITS

- Quick and easy to install
- Easy for splicing and maintenance
- Security
- Easy identification
- Total strain relief to the cable
- Provides for additional cable entry

ORDERING INFORMATION

Product No.	Fiber Count	Dimensions		
		Width	Height	Depth
GJH 6200	12, 24	400 mm	360 mm	95 mm
GJH 6300	48	560 mm	460 mm	95 mm
GJH 6400	96	560 mm	440 mm	130 mm

Note:

Each of the above configuration is supplied with customer specified pigtails, adaptors and splice trays.

Features and dimensions of our products stated here are likely to be modified without prior notice, please confirm before placing the order.

